

Vertical Vent Check Valve 1500 serie

Wager's model 1500 vent check valve is mounted vertically on the deck of a ship. In the open position, the valve allows for required ventilation. During heavy seas, our disc style float rises to a neoprene seat, and prevents water and debris from entering tanks and bulkheads. A 30 x 30 or 1/4" x 1/4" mesh stainless steel screen provides protection from deck fires. It is available in galvanized steel, and stainless steel. Special request are needed for aluminum and bronze. Sizes 1.5"-12" threaded, welded, flanged and metric flange.

ABS type approved



SPECIFICATIONS

GALVANIZED STEEL/ ANODIZED ALUMINUM

CONNECTIONS

Threaded (1.5" - 6" only)

Buttweld (1.5" - 6" only)

Flanged (metric available)

Victaulic groove coupling

SIZES

1.5", 2", 2.5", 3", 4", 5", 6",

8", 10" 12", 14"

304 STAINLESS STEEL/ 316 STAINLESS STEEL

CONNECTIONS

Threaded (1.5" - 6" only)

Buttweld (1.5" - 6" only)

Flanged (metric available)

Victaulic groove coupling

SIZES

1.5", 2", 2.5", 3", 4", 5", 6",

8", 10" 12", 14"



Email: info@wager-europe.com

Telephone: +31 343 45 78 63

Web: Wager-europe.com