

Inverted tank air escape valve 1660 serie

The 1660 tank Air Escape Valves allow free passage of air into tanks, dry cargo holds, or storage space. They protect tanks and bulkheads from pressure build-up during loading and unloading of liquid or dry cargo and assure maximum efficiency during operations.

Tank air escape valves do not have a float or automatic closing, they are used in locations not accessible to sea water. All steel castings are hot dipped galvanized.

All aluminum castings are anodized



SPECIFICATIONS

GALVANIZED STEEL / STAINLESS STEEL

CONNECTIONS

Threaded

Buttweld

Socketweld

Flanged (metric available)

SIZES

1.5", 2", 2.5", 3", 4", 5", 6", 8",
10", 12", 14", 16"

Bronze

AVAILABLE IN 90/10
COPPER NICKEL

CONNECTIONS

Threaded

Sil-brazed

Flanged

SIZES

1.5", 2", 2.5", 3", 4", 5", 6", 8",
10", 12"

ANODIZED ALUMINUM

CONNECTIONS

Threaded

Buttweld

Socketweld

Flanged (metric available)

SIZES

1.5", 2", 2.5", 3", 4", 5", 6", 8",
10", 12"



Email: info@wager-europe.com

Telephone: +31 343 45 78 63

Web: Wager-europe.com